H.B.J.	Horizontal Break Joint
H.L.	Horizontal length
H.B.	Half Bevel
H.F.B.	Horizontal Full Bevel
H.H.B.	Horizontal Half Bevel
INT.	Interceptor
INV.	Invert
LAT.	Lateral
LGTH.	Length
L.L.	Laid Length
L.P.	Light Pole
LT.	Left
LOC.	Location
M.B.	Mail Box
MH.	Manhole
MIN.	Minimum
MAX.	Maximum
M.J.	Mechanical Joint
ℳ	Monument Line
NIP.	Nipple
N.	North
No.	Number
PVMT.	Pavement
P.E.	Plain End
P.V.	Plug Valve
PSI	Pounds per Square Inch
ℙ	Property Line
P.C.	Point of Curvature
P.C.C.P.	Prestressed Concrete Cylinder Pipe
P.T.	Point of Tangency
P.I.	Point of Intersection
LBS.	Pounds
P.O.	Push-on
PROP.	Proposed
P.V.A.	Polyvinyl Chloride
RT.	Right
R/W	Right of Way
R.C.P.	Reinforced Concrete Pipe
REQ'D.	Required
REST.	Restrained
RGE.	Range
REV.	Revised-Revision
SH.	Short
$	Section Line
S.	South
SQ. FT.	Square Feet
S.	Spigot

ITEM	CROSS REF.	SPEC. REF.

MIAMI-DADE COUNTY
Delivering Excellence Every Day
WATER & SEWER DEPARTMENT

ISSUE DATE	APPROVED BY
06/01/2008	V.F.C.

STANDARD DETAIL

ABBREVIATIONS FOR DEPARTMENT'S PROJECTS

A
10.0
SHEET 2 OF 3