

- 1. AUTOMATIC AIR RELEASE VALVES ARE REQUIRED UNLESS APPROVED BY DEPARTMENT. MANUAL AIR RELEASE VALVES ARE ONLY USED WHERE GROUND COVER DOES NOT ALLOW FOR AN AUTOMATIC ARV OR AT LOCATIONS REQUIRED TO BLEED THE FM FOR TESTING.
- 2. AIR RELEASE RISER AND PVC PIPE HOUSING SHALL BE PLACED AND MAINTAINED IN VERTICAL POSITION.
- 3. METALLIC THREADS TO BE COATED WITH BITUMASTIC COATING.
- 4. INSTALL TAPPING SADDLE FOR THICKNESS CLASS D.I. MAINS 4" & SMALLER, PRESSURE CLASS D.I. MAINS 8" & SMALLER, OR WHEN MAIN IS PVC, HDPE, OR AC PIPE.
- 5. FOR MANHOLE/VALVE BOX IN GRASS AREAS, SEE SS 21.0 SHEET 1 OF 1.

TYPE "A" MANHOLE	SS 4.0	
ITEM	CROSS REF.	SPEC. REF.

MIAMI-DADE		
COUNTY  Delivering Excellence Every Day		
WATER & SEWER DEPARTMENT		

<u>ISSUE DATE</u>	<u>APPROVED BY</u>
6/29/2011	F.A.
1/22/2019	D.V.

STANDARD DETAIL
MANUAL AIR RELEASE VALVE
ASSEMBLY
IN PAVED AREAS FOR
SEWAGE FORCE MAINS

SS 11.0 SHEET 1 OF 2