

NOMINAL PIPE SIZE	STEEL CASING	THICKNESS SCHEDULE	
4"	12"	.250	
6"	16"	.375	
8"	18"	.375	
10"	20"	.375	
12"	24"	.375	
14"	24"	.375	
16"	30"	.375	
18"	30"	.375	
20"	36"	.375	
24"	42"	.500	
30"	48"	.500	
36"	54"	.500	
42"	60"	.500	
48"	72"	.500	

## **NOTES:**

- 1. A TO-SCALE DRAWING FOR EACH UTILITY MAIN JACK AND BORE IS REQUIRED. ALL RELEVANT DATA MUST BE SHOWN (LENGTH AND SIZE OF CASING, PIPE CONFLICTS, ELEVATIONS, ETC.)
- 2. (\*) DEPTH SHALL BE 36" MINIMUM WITHIN MIAMI-DADE COUNTY AND FDOT RIGHT-OF-WAYS.

				ITEM	CROSS REF.	SPEC. REF.
	<u>ISSUE DATE</u>	<u>APPROVED BY</u>	STANDARD DETAIL		6	
	09/26/2017	D.V.			GS	
MIAMI-DADE COUNTY			CASING		5.0	
Delivering Excellence Every Day			INSTAL	STALLATION		1 of 2
WATER & SEWER DEPARTMENT					SHEET 1	I UF Z